



TILCOR CLASSIC

TECHNICAL DATA



| | |
|--------------------------|------------------------|
| Overall Length | 1320 mm |
| Length of Cover | 1265 mm |
| Overall Width | 415 mm |
| Width of Cover | 369 mm |
| Minimum Pitch | 12° (21%) |
| Up stand | 26 mm |
| Down turn | 24 mm |
| Roof Cover | 0.467 m ² |
| Tiles per m ² | 2.14 |
| Weight/panel | 2.90 kg |
| Weight/area | 6.56 kg/m ² |
| Batten space | 369 mm |

MATERIAL STRUCTURE



- 1 Overglaze
- 2 Stone Chip
- 3 Basecoat
- 4 Transparent Acrylic Coating
- 5 Aluminium-Zinc alloy
- 6 Steel
- 7 Aluminium-Zinc alloy
- 8 Transparent Acrylic Coating

TEXTURED SURFACE

Stone chip granules are applied to provide an attractive textured finish which at the same time enhance resistance to UV radiation.

COATING SPECIFICATION

Overglaze: Clear 100% acrylic resin coating for granule binding and a semi-gloss finish. It helps enhance the appearance as well as increase the resistance to physical damage.

Stone Chip: Carefully selected granules provide excellent surface coverage and attractive natural lasting colours.

Basecoat: A tough opaque coating based on acrylic resin. It bonds the stone chips and protects the underlying layer from water and UV radiation. It has good UV resistance and retains its flexibility although it does become harder after the first few weeks.

Transparent coatings: Both sides of the Aluminium-Zinc alloy coated steel are coated with a transparent layer that provides protection and a uniform substrate for further coatings. This transparent coating allows identification of the Aluminium-Zinc substrate to be made by distributors and customers.

STEEL SPECIFICATION

The TILCOR CLASSIC tile is made of Aluminium-Zinc alloy coated steel. The grade of steel used is designed to allow forming without cracking or significant elastic recovery and at the same time to be rigid enough to tolerate reasonable loads without excessive deformation.

| | |
|------------------------------|----------------------|
| Nominal Thickness | 0.43 mm |
| Steel Grade | S280GD |
| | G300 |
| Aluminium-Zinc Coating Mass | 150 g/m ² |
| Aluminium-Zinc Coating Grade | AZ150 |

COLOURS

